

8-AXLE LIVE BOTTOM CONSTRUCTION TRAILER



# Construction

## 8-Axle Live Bottom Trailer



8-AXLE LIVE BOTTOM CONSTRUCTION TRAILER





# 8-Axle Live Bottom Construction Trailer

## Live Bottom Features Include:



**Sloped walls (60°)** reduce load segregation during transport and eliminate bridging problems.


**Continuous Belt** of heat- and oil-resistant two-ply rubber moves the entire load to rear for discharge.



The 36-inch belt is attached to steel slats and moved by double pitch roller chain on steel tracks.



**Proprietary Roller Chain** with self-lubricating chain oiler system.




**Dual Direct Hydrostatic Drive** with double-reduction planetary gearbox eliminates the problems associated with chain drives.



**Easy Access to Belt** with standard hydraulic hook-ups and **replaceable king pin**.



**Lift Suspension**, front lift bags (standard).



**Electric Cab Control**, (standard) and rear over-ride with axle lift and tailgate control.



**Capable of 50 Ton+ Payloads – Michigan Load Regulations**



**Two-Speed Crank-Up Landing Legs**, (standard).



**Flip Up Mud Flaps**, removable convenient hinged design for better paver hopper clearance.



**Locking Tailgate**, with lift package (standard).

**The Trail King 8-Axle Live Bottom** provides exceptional hauling versatility of asphalt and asphalt-related materials and is designed to meet stringent weight-load restrictions.

**Clean and efficient horizontal discharge** in one revolution or less makes unloading easy and reduces cycle time. Plus, it reduces concerns about unloading on job sites with limited clearance or uneven terrain. Horizontal discharge eliminates tipping concerns while unloading. Since the hopper does not raise, power lines and overhead obstacles pose no special risk.

## Specifications

Model	OLB840NG-HH
Capacity	48 cu. yds.
Overall length	44'9"
Overall height	10'6"
Overall width	102"
King pin height	49"
King pin to center of last axle	40'
Number of Axles	8
Empty weight ±3%	30,100 lbs.

## Optional Features

- Tarp systems – manual and electric.
- Aluminum sheeting/insulation.
- Flow control valve.
- Gravel service belt in lieu of heat and oil resistant.
- Tire and wheel options.
- Paint options.

All dimensions are approximate and are subject to change without notice. Trailers pictured may include options.

**1-800-762-5557**

**8-AXLE LIVE BOTTOM CONSTRUCTION TRAILER**