

VOLVO AUTO HAULER (VAH)



FEATURES

BENEFITS

Volvo SCR No Regen engines



Up to 5% improvement in fuel efficiency over EPA 2007 engines. Available with Volvo D11 or D13 engines. Horsepower from 325 to 500 HP and torque from 1250 to 1750 lb-ft

Idle Emission Certification



Standard on all Volvo models; meets California low NOx idle requirements, including all add-in states

Available with Volvo I-Shift transmission



Monitors vehicle changes and selects the best, most efficient gear for maximum comfort and fuel efficiency

Quiet and spacious cab



Improves driver alertness and provides a comfortable ride. Extra room between seats and storage for personal gear

Ergonomic instrument panel



Controls within safe and easy reach help to reduce driver fatigue

Set-forward axle



Improves weight distribution with excellent maneuverability

Clean top of frame behind the cab




Quick body mounting and easy hookups reduce lead time



VOLVO AUTO HAULER SPECIFICATIONS

| | |
|------------------------------------|--|
| BBC | 113.6" (2885 mm); Medium hood |
| Front Axle Position | 29.1" (739 mm) set-forward axle |
| Cab Versions | Standard Daycab Height Lowered Daycab Height available through Fontaine Modification Company* |
| Gross Vehicle Weight Rating (GVWR) | 52,600 lbs |
| Engines | Volvo D11; 325-405 hp @ 1250-1450 lb-ft Volvo D13; 375-500 hp @ 1450-1750 lb-ft |
| Transmissions | Volvo ATO I-Shift; 12 speed Eaton® Fuller® FRO 10 speed; manual |
| Front Axle | Volvo VF14 deep drop axle |
| Front Suspension | Parabolic leaf spring; 14,600 lb capacity |
| Front Wheels | Standard 22.5" x 9.00" hub piloted wheels; steel or aluminum availability |
| Front Tires | Low profile 295/60R22.5 tires |
| Rear Axle | Arvin Meritor MT-40-14X3C Amboid; 40,000 lb capacity |
| Rear Suspension | Low Height Volvo Air Suspension; 38,000 lb capacity |
| Rear Wheels | Aluminum hub piloted 19.5" x 7.50" wheels |
| Rear Tires | Low profile 265/70R19.5 tires |
| Frame Rail Packages | 10.47" x 3.54" x .31" Straight Steel Rails 1,778,400 in-lb RBM |
| Fuel Tanks | 125 gallon driver-side-mounted fuel tank |
| Interior Trim Packages | Three interior trim levels: Choice Vinyl, Rally Fabric, Touring Fabric Seat upholstery: Vinyl, Fabric and Leather |

*The lowered daycab height version has not been subjected to the Swedish Impact Test requirements.



Volvo D13

Lightweight, heavy-duty performance. Built for reliability and economy, the Volvo D13 delivers impressive performance without the weight.



I-Shift

Integrated seamlessly with all Volvo Power engines, the Volvo I-Shift maximizes driver comfort, payload and fuel economy.

Volvo Trucks North America
PO Box 26115
Greensboro, NC 27402-6115

www.volvotrucks.us.com

Volvo Trucks Canada
2100 Derry Road West, Suite 410
Mississauga, Ontario L5N 0B3

©2011 Volvo Group North America, LLC
PV835-975

VOLVO